

DC-250



Single phase motor and direct transmission, 1.1 kW (1.5 hp) with thermal protector.
 Water pump cooling blade with flow control.
 Chassis of great structural rigidity
 Tailstock on bearings and hinged at 45° for miter cuts.
 Includes diamond disc CEV PRO Ø 250 mm.
 Cable not included.



REF.



DC-250 1200 55941	230V-50 Hz.	1	**1	2790	120,5 cm	85x85 cm	171x79x131 cm	61 / 90 mm	∞ cm	Yes	250 mm	60 kg	75 kg	Yes
DC-250 1200 55942	220V-60 Hz.	1	**1	2790	120,5 cm	85x85 cm	171x79x131 cm	61 / 90 mm	∞ cm	Yes	250 mm	60 kg	75 kg	Yes
DC-250 1200 55943	110V-50 Hz.	1	**1	2790	120,5 cm	85x85 cm	171x79x131 cm	61 / 90 mm	∞ cm	Yes	250 mm	60 kg	75 kg	Yes
DC-250 1200 55944	120V-60 Hz.	1	**1	2790	120,5 cm	85x85 cm	171x79x131 cm	61 / 90 mm	∞ cm	Yes	250 mm	60 kg	75 kg	Yes
DC-250 1200 55947	120V-60 Hz.	1	**1	2790	120,5 cm	85x85 cm	171x79x131 cm	61 / 90 mm	∞ cm	Yes	250 mm	60 kg	75 kg	Yes



©RUBI 2014 rubi.com